

Evaklenz601

gp sugar soap powder

Description & Uses:

Evaklenz601 is a gentle yet powerful alkaline cleaner for general purpose cleaning including all painted surfaces. Evaklenz601 is used for removing grease and grime (including crayon and ink marks) from paint film without attacking or destroying the paint film itself; removal of grease and grime off walls prior to painting; degreasing of floors; cleaning drains; general household cleaning including sinks, basins, floors, etc.; cleaning of tiles in kitchens, bathrooms, showers, etc.

Evaklenz601 is very economical multipurpose cleaning agent to use since a dilution of 1 cup makes a 5lt solution. Evaklenz601 contains no caustic soda & is suitable for use on brick, concrete, cement plaster, ceramic tiles, metal, painted surfaces (either emulsion paint or enamel), vinyl flooring etc.

Mixing details:

- For general household cleaning:
Dissolve ½ cup Evaklenz601 in 5lts hot water.
- For difficult surfaces:
Dissolve 1 cup Evaklenz601 in 5lts hot water.

Application method:

Dab solution onto surface to be cleaned using a cloth or sponge. Allow it to soak into the dirt.

Wipe with a damp cloth.

Repeat if necessary - do not scrub surface as this will damage the paint film.

Rinse surface with clean water to remove all traces of Evaklenz601 and dab dry.

Application instructions:

- For cleaning basins:
 1. Sprinkle a little Evaklenz601 on a damp cloth.
 2. Wipe over surface.
 3. Rinse with clean water.
- For cleaning toilets:
 1. Sprinkle a little Evaklenz601 into the toilet bowl.
 2. Leave to stand for about one hour, then flush.
 3. Repeat if necessary.
- For cleaning drains:
 1. Dilute 1 tablespoon of Evaklenz601 in 500 ml hot water.
 2. Pour down drain while still hot.
 3. Repeat if necessary.
- For cleaning garage floors with oil stains:
 1. Sprinkle Evaklenz601 over the oil.
 2. Sprinkle with clean water and allow to stand for 30 minutes.
 3. Scrub clean with broom.
 4. Rinse with clean water.
 5. Repeat if necessary.



| | |
|----------------------------|---------------------|
| <u>Appearance:</u> | Free flowing powder |
| <u>Colour:</u> | White |
| <u>Pack size:</u> | 5kg packets |
| <u>Mass solids:</u> | 100% |
| <u>S G:</u> | 1.68 |
| <u>PH:</u> | N/A |
| <u>Flash point:</u> | N/A |

Safety:

Safety should always be a priority when working with materials and tools - Avoid contact with eyes - Do not ingest or inhale.
Clean-up with clean water.

Environment:

Always recycle when able to.
Do not put materials in drains or waterways.

Technical Information:

We provide free comprehensive technical back-up service on all of our products and we guarantee that our products will comply with the technical properties detailed in their specific Technical Data Sheets issued by ourselves.

To the best of our knowledge and belief, this information is true and accurate. As the conditions of use and any labour involved are beyond our control, the end-user must satisfy himself by prior testing that the product is suitable for his specific application.

Products are sold subject to our Standard Conditions of Sale.

Evachem Construction Chemicals (Pty) Ltd

PO Box 1159, Wandsbeck, 3630 | 4 Dinkelman Road, New Germany, 3610

Tel: 0861 EVACHEM / 0861 382 2436 | Fax: 031705 3884

info@evachem.co.za - www.evachem.co.za

